

LESSEY Marine Services, Inc.

P.O. Box 23734 • Harahan, Louislana 70183

Phone: (504) 734-1156

Fax: (504) 734-1195

BARGE VAPOR TIGHTNESS TEST LETTER

NOTE: Test results are valid for one (1) year from date of test.
NOTE: This test was performed with a certified and calibrated gauge by the testing facility.
NOTE: The vapor stack flame screen was verified to be clean and defect free.
NOTE: THE Vapor statement of the stateme
■ Test date: <u>2-2-2024</u>
■ Barge name / Official Number: WEB 311
Maximum load rate (BPH): 5000 bbl / hr
→ Pressurize cargo tanks and vapor system to 28 inches of water using a Manometer to record the time and pressure. Close all air valves and allow the vessel to remain pressured for 30 minutes. Use soap to test and inspect for leaks. After 30 minutes, record pressure and times.
→ Test cargo tanks & Vapor System to ② & inches of water. → Start Time: 13:00 Beginning Pressure: ② & → End Time: 13:30 Ending Pressure: ② 7 9 ✓ This vessel has been tested in accordance with Section 40 CFR 61.304(f) and has been found to be vapor tight.
ompany of Tester; Location:
BMS QUED Fleet
ame of Tester (print): Signature of Tester:
Krith Kristoff hat Much
ame of Witness (print): Signature of Witness:
Practes Diascraienski Diascraienski
filiation / Company of Witness (print)
PMS
<u> </u>

BLESSEY MARINE SERVICES, INC.