



BLESSEY

Marine Services, Inc.

P.O. Box 23734 • Harahan, Louisiana 70183

Phone: (504) 734-1156

Fax: (504) 734-1195

BARGE VAPOR TIGHTNESS TEST LETTER

NOTE: Test results are valid for one (1) year from date of test.

NOTE: This test was performed with a certified and calibrated gauge by the testing facility.

NOTE: The vapor stack flame screen was verified to be clean and defect free.

- Test date: 11-8-23
- Barge name / Official Number: WEBL106 1217927
- Maximum load rate (BPH): 5000

→ Pressurize cargo tanks and vapor system to 28 inches of water using a Manometer to record the time and pressure. Close all air valves and allow the vessel to remain pressured for 30 minutes. Use soap to test and inspect for leaks. After 30 minutes, record pressure and times.

→ Test cargo tanks & Vapor System to 28 inches of water.

→ Start Time: 1000 Beginning Pressure: 28

→ End Time: 1030 Ending Pressure: 27.5

✓ This vessel has been tested in accordance with Section 40 CFR 61.304(f) and has been found to be vapor tight.

Company of Tester:	Location:
<u>Blessey Marine</u>	<u>Web FIT</u>
Name of Tester (print):	Signature of Tester:
<u>Keith Kristoff</u>	<u>[Signature]</u>
Name of Witness (print):	Signature of Witness:
<u>Charles Barzienski</u>	<u>[Signature]</u>
Affiliation / Company of Witness (print):	
<u>Blessey Marine</u>	

