



BARGE "WEB 213"

INNAGE TRIM TABLE

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 CENTER	00-3/8	- 00-3/8	00-7/8	- 00-7/8	01-1/4	- 01-1/4	01-5/8	- 01-5/8	02-0/8	- 02-0/8	02-1/2	- 02-1/2
2 PORT	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8
2 STBD	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8
3 PORT	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8
3 STBD	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8
4 CENTER	- 00-1/2	00-1/2	- 01-0/8	01-0/8	- 01-1/2	01-1/2	- 02-0/8	02-0/8	- 02-1/2	02-1/2	- 03-0/8	03-0/8

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"
 AFT DRAFT = 4'-00"
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 1 CENTER IS - 00-7/8"
 FOR A MEASURED INNAGE GAUGE OF 4'-00" ON 1 CENTER, THE TRIM CORRECTED INNAGE IS 3'-11 1/8"

LENGTH BETWEEN DRAFT MARKS: 234'-00"

May 5, 2009

**PRECISION MEASUREMENT
& ANALYSIS, INC.**

P.O. Box 2092
 Pearland, Texas 77588

<http://www.pmacorp.net>