



# BARGE "WEB 304"

## ULLAGE TRIM TABLE

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 PORT	00-1/8	- 00-1/8	00-1/4	- 00-1/4	00-1/2	- 00-1/2	00-5/8	- 00-5/8	00-3/4	- 00-3/4	00-7/8	- 00-7/8
1 STBD	00-1/8	- 00-1/8	00-1/4	- 00-1/4	00-1/2	- 00-1/2	00-5/8	- 00-5/8	00-3/4	- 00-3/4	00-7/8	- 00-7/8
2 PORT	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8
2 STBD	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8	00-0/8
3 PORT	- 00-1/8	00-1/8	- 00-1/4	00-1/4	- 00-1/2	00-1/2	- 00-5/8	00-5/8	- 00-3/4	00-3/4	- 00-7/8	00-7/8
3 STBD	- 00-1/8	00-1/8	- 00-1/4	00-1/4	- 00-1/2	00-1/2	- 00-5/8	00-5/8	- 00-3/4	00-3/4	- 00-7/8	00-7/8

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"  
 AFT DRAFT = 4'-00"  
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 1 PORT IS - 00-1/4"  
 FOR A MEASURED ULLAGE GAUGE OF 4'-00" ON 1 PORT, THE TRIM CORRECTED ULLAGE IS 3'-11 3/4"

LENGTH BETWEEN DRAFT MARKS: 237'-00"

May 10, 2009

PRECISION MEASUREMENT  
& ANALYSIS, INC.

P.O. Box 2092  
Pearland, Texas 77588

<http://www.pmacorp.net>